

Technical Specifications

Display	Size	40-inch-class widescreen (39 1/2 inch diagonal) TFT LCD
	Max. Resolution	1,920 x 1,080 pixels
	Installation	Landscape / Portrait / Face-Up
	Brightness*2	300 cd/m ²
	Pixel Pitch (H x V)	0.45735 x 0.4494 mm
	Contrast Ratio	5,000 : 1
	Viewing Angle (H/V)	178°/178° (CR≥10)
	Backlight	LED, edge lit
	Response Time	9.5 ms (grey to grey, avg.)
	Active Screen Area	878.1 x 485.3 mm (34 9/16" x 19 3/32")
Connectivity	Input Terminals*5	PC analogue: Mini D-sub 15-pin x 1, HDMI x 2 (HDCP and 1080p compatible, PC/AV signal compatible), DisplayPort (HDCP compatible, PC signal compatible) x 1, LAN port (10Base-T/100Base-TX) x 1
	Output Terminals*5	3.5 mm-diameter mini stereo jack x 1
Touchscreen	Touch Technology	Capacitive touch technology
	Touch Points	10 points
	Protection Glass	Thickness: Approx. 3.8 mm*3 Shock resistance: 130 cm*4
General	Speaker Output	10 W + 10 W
Power	Power Supply	100V – 240V AC, 50/60 Hz
	Power Consumption	89 W
Operation Condition	Operating Temperature	5°C to 35°C
	Operating Humidity	20% to 80% RH (no condensation)
Dimension (W x D x H) (approx.) (Display only)		939 x 65 x 546 mm
Weight (approx.)		17.5 kg (38.6 lbs)